Architectural Shapes

Molded Polystyrene Insulation.

Foam-Control® molded polystyrene insulation includes an ingredient you won't find in other molded polystyrene products. Control. Foam-Control insulation gives you control over the design of your project. You determine the shape and specs of the molded polystyrene components you need, then your Foam-Control molded polystyrene supplier works with you to deliver them on time and within budget.

- R-value that never changes and is stable over time
- Range of compressive strengths available
- · Closed cell insulation with superior moisture resistance
- · High drying potential to rapidly release absorbed moisture
- Preferred component for architectural shapes

Strength/R-value.

FOAM CONTROL .	Compressive Strength ¹ , psi	R-value/inch ²	
		75°F³	40°F⁴
100	10	3.9	4.2
130	13	3.9	4.3
150	15	4.2	4.6
250	25	4.4	4.8

¹ Compressive strength @ 10% deformation.

Proven to meet, or exceed, building codes.

Foam-Control is manufactured under an industry leading quality control program monitored by UL and further recognized in UL Evaluation Report UL ER11812-01. Foam-Control meets ASTM C578, "Standard Specification for Rigid, Cellular Polystyrene Thermal Insulation".



Custom Fabrication.

Foam-Control insulation shapes are custom fabricated by hot wire cutting with computer aided design, and if necessary, assembled together to provide a solution specific to your needs.

Foam-Control insulation means that you can achieve product designs that wouldn't be possible with other materials.





FOAM FACTS:

Foam-Control Architectural Shapes.

- Foam-Control Architectural Shapes can create effective 3-D architectural shapes
- Foam-Control Architectural Shapes meet strength requirements at a lower cost and are available in a range of densities/types
- Foam-Control Architectural Shapes are well suited for lower volume items and are compatible with exterior finish coatings

² R-value units are °F·ft²·h/Btu. ³ Recommended for design in WARM climates.

⁴Recommended for design in COLD climates.

Performance Value.

When you consider all performance characteristics and cost, Foam-Control is your best choice for foam insulation.

Foam-Control has air in its closed cells and therefore has a stable R-value. Many other insulations use blowing agents that cause R-value loss and are harmful to the environment.

Foam-Control has compressive strength to meet specific project requirements.

Foam-Control is manufactured to resist moisture absorption in wetting conditions and release absorbed moisture quickly during drying periods, which means Foam-Control maintains R-value.

Termite Resistant - @Perform Guard®.

One of the most destructive forces anywhere is termites. Foam-Control can be manufactured with Perform Guard, a proven and safe additive, that effectively resists termites.

Foam-Control with Perform Guard meets ICC ES AC239, "Acceptance Criteria for Termite-Resistant Foam Plastics".

Recyclable.

After it's life as a building insulation, Foam-Control is 100% recyclable. It can be ground into granules and reincorporated into new Foam-Control products or it can be thermally processed into a resin that's used to manufacture other new products.

Ready to take control? Start here.

If you're ready to have Foam-Control contribute to your next project, just contact your nearest Foam-Control manufacturer and Technical Sales Representative. They will be happy to give you design consultation, information about Foam-Control products, pricing, and answers to all of your questions.



PACIFIC ALLIED PRODUCTS Ltd.

MADE IN HAWAI'I, FOR HAWAI'I SINGE 1965
CAMPBELL INDUSTRIAL PARK
91-118 KAOMI LOOP KAPOLEI, HAWAII 96707
808-682-2038 888-824-3626
WWW.HAWAIIANFOAMCONSTRUCTION.COM









Foam-Control products are manufactured by AFM Corporation licensees.

Copyright © 2019 AFM Corporation. All rights reserved. Printed in USA. Foam-Control, the Foam-Control logo and Perform Guard are registered trademarks of AFM Corporation, Lakeville, MN.

UL logo is a registered trademark of UL LLC. USGBC logo is a registered trademark of U.S. Green Building Council.

FC12-01/19

